

# Arc

## AS-22

Passive subwoofer for fixed installations, 12", 500 W, 127 dB SPL  
max., 38 Hz – 500 Hz, 520 × 420 × 430 mm



# Arc AS-22

The AS-22 is a compact, passive subwoofer for fixed installations. It perfectly complements the compact fullrange speakers of the Arc and Linea series in the low end. It is characterized by precise sound, high power rating and attractive design.



## Main features

- 12" long excursion driver
- 500 W nominal power rating
- Vented enclosure with non-turbulent port design (Fohhn NTP)
- SPL max.: 127 dB
- Connections: 2 × 4-pin terminal
- High-quality wooden enclosure (multiplex birch)
- Available in RAL Classic, NCS or Pantone colors on request
- Optionally available with weatherproof PU coating
- Various mounting options
- In order to ensure performance and operational safety, Fohhn system amplifiers including the correct speaker preset are required.



## Available with the following color options



Black



White

## Equipped with the following Fohhn technologies



Special colors  
optional



Ball impact  
resistant

# Technical data

## Electroacoustic features

acoustic design	bass reflex, NTP (Non-Turbulent Port design)
power rating (nominal)	500 watts
components	1 × 12" long excursion
maximum SPL	127 dB
frequency range	38 Hz – 500 Hz
nominal impedance	4 ohms

## Physical features

enclosure	multiplex birch plywood
connectors	2 × 4-pin terminal
dimensions (w × h × d)	520 × 420 × 430 mm
weight	21 kg
standard colours	black, textured paint
front design	acoustic foam in housing colour
protection grille	steel grille, ball impact resistant, powder-coated
mounting points	6 × M6 thread

## Optional features

optional colours	RAL Classic / NCS / Pantone on request
optional weather protection	polyurethane coating, water-repellent speaker cone impregnation

power rating (nominal/program): according to IEC-60268-5 (long term/short term)

power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset

frequency range: -10 dB under anechoic halfspace-conditions with speaker preset

weight: net weight without optional equipment

**Fohhn Audio AG**  
**Großer Forst 15**  
**72622 Nuertingen**  
**Germany**

**Phone +49 7022 93323-0**  
**Fax +49 7022 93324-0**  
**[www.fohhn.com](http://www.fohhn.com)**  
**[info@fohhn.com](mailto:info@fohhn.com)**

