


**Fohhn**  
colors of sound

Datasheet

# Linea LC-100



## Linea LC-100

The LC-100 is a passive line source speaker for fixed installations. It is optimized for excellent speech reproduction and is ideally suited to both indoor and outdoor applications thanks to its weatherproof aluminum enclosure. The renowned Fohhn line source speakers combine the advantages of line arrays – such as directionality, homogeneous dispersion and reach – in a compact system. The slim aluminum housing enables perfect visual integration into the room architecture.



- 8 × 4" driver
- Nominal power rating: 240 W
- Frequency range: 120 Hz – 12 kHz
- Suppression of unwanted side lobes thanks to Fohhn Source Division Waveguide
- Perfect speech intelligibility and long reach
- Low impedance technology
- Weatherproof without additional protection (degree of protection IP54 according to IEC 529 / EN 60529)
- Available in different colors (RAL Classic, Pantone, NCS) or with Fohhn Texture Design
- In order to ensure performance and operational safety, Fohhn system amplifiers including the correct speaker preset are required.

Available with the following color options



Black



White

Equipped with the following Fohhn technologies



Fohhn Texture Design



Fohhn Source Division Waveguide



Special colors optional



Weather-resistance possible

# Technical data

## Electroacoustic features

acoustic design	weatherproof passive loudspeaker, closed, passive 2-way CD crossover, suppression of side lobes by Source Division Waveguides
power rating (nominal)	240 watts
power rating (program)	480 watts
power rating (peak)	960 watts
components	8 × 4" treated drivers
sensitivity	98 dB SPL
maximum SPL	127 dB SPL
frequency range	120 Hz – 12 kHz
2-way design	yes
nominal impedance	8 ohm
nominal dispersion (h × v)	130° × 15°

## Physical features

enclosure	weatherproof aluminium housing, powder coated, steel bracings
connectors	screwed terminal connectors capable of receiving up to 4 mm <sup>2</sup> , two per pin, terminal cover with dual cable gland for up to 10 mm cable diameter
dimensions (w × h × d)	approx. 133 × 990 × 128 mm
weight	8 kg
standard colors	black (RAL 9005) or white (RAL 9016), powder coated
weather protection	as standard (protection class IP54, in accordance with IEC 529 / EN 90529)
front design	ball impact resistant grille, galvanized and powder coated in enclosure colour, backed by acoustically transparent foam
mounting points	T-slot on the rear

## Optional features

special colors	RAL Classic / NCS / Pantone on request, Fohhn Texture Design
optional connectors	ceramic terminals capable of receiving up to 2.5 mm <sup>2</sup>
optional weather protection	protection class IP54, weatherproof without additional protective measures

## CAAD simulation data

simulation data	EASE, CLF, Ulysses, Fohhn Designer
-----------------	------------------------------------

power rating (nominal/program): according to IEC-60268-5 (long term/short term)  
power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset  
sensitivity: 2,83 V at 8 ohms (2 V at 4 ohms, 4 V at 16 ohms) at a distance of 1 m under anechoic fullspace conditions  
weight: net weight without optional equipment  
nominal dispersion: -6 dB compared to the main dispersion axis

Fohhn Audio AG  
Großer Forst 15  
72622 Nürtingen  
Germany

Phone +49 7022 93323-0  
Fax +49 7022 93324-0  
[www.fohhn.com](http://www.fohhn.com)  
[contact@fohhn.audio](mailto:contact@fohhn.audio)



Fohhn Audio AG reserves the right to make changes to its product design and technology without notice. All information is subject to change.  
© 2026, Fohhn Audio AG, Germany.

Document version: 2026-01-29 13:26:13