

ASP-01 USB Speakerphone

For personal and small group conference

ASP-01 conference speakerphone is specially designed home based worker, on-line education, and small business conference room, to replace the PCs and mobile phone's speaker and microphone with outstanding audio quality.

- Simply Plug and Play

Easy connect to your PC or laptop via USB 2.0, works great with PC based communication softphone i.e Skype

-Compact and portable design

You can join the conversion anywhere anytime, regardless of your location or your schedule.

- Integrate with video conference system

Professionally designed to work with video conference systems, provide perfect and cost-effective audio solution to your video conferences.

-Enjoy crisp, clear and rich audio play back

Full bandwidth frequency response and advanced Crystal Sound audio processing technologies deliver remarkably rich full audio for natural, effortless conversations.

-Save time and convenient

It is more easier to allow you to decide where and how you want to meet ,in office , home or in a hotel room while you are away from the office . It is a convenient device.



Product Specifications Sheet

Recommended Situations Recommended room coverage Conference size 3-5 persons Microphone Sound pick up range Microphone response frequency 30-16KHz	
Recommended room coverage 10-15m² Conference size 3-5 persons Microphone 2m Microphone response frequency 30-16KHz	
Conference size 3-5 persons Microphone Sound pick up range 2m Microphone response frequency 30-16KHz	
Microphone Sound pick up range Microphone response frequency 2m 30-16KHz	
Sound pick up range 2m Microphone response frequency 30-16KHz	
Microphone response frequency 30-16KHz	
1 1 2	
Built-in Mic 3	
Expandable Mic N/A	
Speaker	
Max output(dB) 83dB	
Speaker response frequency 30-16KHz	
Audio	
Full Duplex √	
Dynamic Noise Reduction (DNR) √	
Automatic Gain Control (AGC) √	
Connectivity	
USB cable √	
Bluetooth connectivity N/A	
Package	
Unit Dimensions Ф140 x 32mm	
Package Dimensions 245x170x50mm	
Weight 0.5kg	
Accessories Protective Travel Case USB cable,English User's Manual	
Environments	
System requirements windows XP windows Vista windows 7/8/10	
Power Input USB:5 V DC @ 300 mA Maximum	
Operating temperature 5℃—40℃	
Storage temperature -30 °C —55 °C	
Rechargeable battery N/A	
Compliance FCC / CE / RoHS	