



Fohhn
colors of sound

Datasheet

Focus Modular DFM-400



AES/EBU

AIREA

Focus Modular DFM-400

DFM-400 is an active low-mid module with Fohhn Beam Steering technology. It can be flexibly combined with the high frequency modules DFM-100 / DFM-110. The new generation of our renowned Focus Modular system is now fully digitized and provides further developed Fohhn DSP and digital signal connections. Acoustically redesigned and equipped with even more powerful drivers, DFM delivers excellent, audiophile sound and best speech intelligibility. A high-quality and high-performance solution for larger conference rooms, theaters and even open-air concerts. And all of this with an enclosure that is just about 22 cm wide and can be flown straight and integrated seamlessly thanks to beam steering.



- 32 x 4" long excursion speakers, neodymium
- 16 integrated class-D amplifiers
- Optimized Fohhn DSP structure inside
- Fully digital signal flow from input to amplifier
- Q-SYS Plugin available in combination with Fohhn NA-4 or ABX-6
- Max. SPL single module: 134 dB (94 dB @ 100 m)
- Frequency range: 55 Hz – 1,7 kHz
- Vertical dispersion controlled in real time via Fohhn Audio Soft
- Vertical beam width: 0° to 90°, sound inclination angle: -40° to +40° (adjusted in 0.1° increments)
- Two separate beams can be controlled
- Fohhn Side Lobe Free Technology
- Easy rigging thanks to the Fohhn Quicklock System

Available with the following color options



Black



White

Equipped with the following Fohhn technologies



Fohhn Beam Steering Technology



Fohhn Airea



Fohhn DSP inside



Flyable product



Special colors optional



Auto Power Save

Possible input interfaces for this product

AES/EBU

AIREA®

Technical data

Electroacoustic features

acoustic design	electronically steerable line array speaker
components	32 × 4" long excursion speakers, neodymium
maximum SPL	134 dB (94 dB @ 100 m)
operational mode	active, 16-channel DSP-amplifier, Class-D
frequency range	55 Hz – 1.7 kHz
horizontal dispersion	90°
vertical beam width, digitally controlled	0° – 90° in 0,1° increments
vertical inclination angle, digitally controlled	-40° – +40° in 0,1° increments
acoustic centre	0% (bottom) to 100% (top) movable, both beams

Physical features

enclosure	multiplex birch plywood, Aluminium
dimensions (w × h × d)	224 × 1636 × 274 mm
weight	42 kg
standard colors	textured paint / powder coating, black
front design	hexagonal perforated steel grille in enclosure colour, backed by acoustically transparent foam
protection grille	steel grille, ball impact resistant, powder coated
mounting points	integrated flying tracks, 4 × M8-threads at rear

Optional features

special colors	RAL Classic / NCS / Pantone on request
----------------	--

CAAD simulation data

simulation data	Fohhn Designer
-----------------	----------------

Electronic features

amplifier type	Pure Path Digital PWM
audio inputs	AES/EBU
audio outputs	AES/EBU
amplifier power	16 × 120 W
DSP channels	16
frequency response	20 Hz – 20 kHz
signal/noise ratio	>105 dB/A
auto power save	adjustable from 1 s to 12 h, or never active
protective circuit	soft start, overtemperature, short circuit, overload
power supply	100 V – 240 V AC 50/60 Hz, power supply with Power Factor Correction (PFC)
inrush current	7,5 A (230 V) / 3,8 A (115 V)
power consumption	500 W RMS, idle 30 W, standby 10 W
heat dissipation	150 W, 517 BTU/h, 129 kcal/h
operating temperature	0 – 40° C
cooling	temperature-controlled fan
weight (electronics)	6 kg

Controller

digital signal processors	2
independent limiters	6
FIR filter	yes
gain	-80 dB – +12 dB
EQ	10-band parametric EQ, gain, +/-12 dB, frequency 10 – 20 kHz, Q 0.1 – 100
selective 3-band limiting	bass / mid / high
limiter / compressor	yes
noise gate	yes
delay	input: 0 – 350 ms (0 – 120 m); output: 0 – 640 ms (0 – 220 m)
X-over	Linkwitz-Riley 4th order (24 dB / octave), high pass 10 Hz – 20 kHz, low pass 10 Hz – 20 kHz
system latency	1.2 ms
band-specific time constants	yes
filter technology	80-bit double precision
input	AES/EBU 32 kHz – 96 kHz, 16/24 bit
input DSP processing	yes

Remote control and remote monitoring

remote control	Fohhn Audio Soft, Fohhn Net
remote monitoring	temperature, protect, power supply, Fohhn Net, Fohhn Audio Soft, AES/EBU signals
simulation beam	Fohhn Net, Fohhn Audio Soft

Connections and controls

controls	mains switch (remote-controllable via Airea Connect)
mains connection	1 × PowerCON mains in, 1 × PowerCon mains out
inputs	1 × etherCON Airea Connect / stack link, 1 × XLR AES/EBU, 1 × etherCON Fohhn Net
outputs	1 × etherCON stack link, 2 × XLR AES/EBU, 2 × etherCON Fohhn Net
signal inputs	AES/EBU 32 kHz – 96 kHz, 16/24 bit
signal outputs	AES/EBU link-out from input

Display LEDs

Sign LED (connector panel and front grille)	blue = power on, blue flashing = sign
status LED	green = ready, red = protect / standby, red flashing = fault
receive / send LED	receive / send remote control LED
audio error LED	red = no AES/EBU
remote power LED	green = Airea Connect active, remote power on
on (stack link) LED	green = stack link active

power rating (peak); maximum SPL: peak, 20 ms with bandpass filtered pink noise signal according to IEC 60268-2 at one octave above the lower limit of the frequency range, with speaker preset
frequency range: -10 dB under anechoic halfspace-conditions with speaker preset
weight: net weight without optional equipment
heat dissipation: pink noise, 6 dB crest, 1/4 Pmax
nominal dispersion: -6 dB compared to the main dispersion axis

Fohhn Audio AG
Großer Forst 15
72622 Nürtingen
Germany

Phone +49 7022 93323-0
Fax +49 7022 93324-0
www.fohhn.com
contact@fohhn.audio



Fohhn Audio AG reserves the right to make changes to its product design and technology without notice. All information is subject to change.
© 2026, Fohhn Audio AG, Germany.

Document version: 2026-01-29 13:06:06