


ATO-01
TORPEDO



User Manual
V1.0

Explanation



1. Optical Glass Lens
2. LED Indicator Light
3. Silicon Privacy Lens Cover
4. Microphone
5. Built-in Bracket Mount
6. Accessory Mounting Receiver
7. USB Type-C Port

Product Features

Image Sensor	1/2.8" 8MP Ultra high definition CMOS sensor.
FOV	80° (Diagonal); 65° (Horizontal).
Min. Distance	10cm
Zoom	3x Zoom
Autofocus	Accelafocus Phase Detection
ePTZ	Supported

Supports both Landscape and Portrait Video Displays.
Flexibility to meet any application.

USB Type-C Port

A USB Type-C cable provides video output camera control, power supply, and program upgrades.



USB power supply



Upgrade




4K@30 and 1080@60



USB Type-C port

Connection



1. Connect your computer to the webcam via the included USB Type-C cable (1m).
2. Plug and play, no need to install any drivers. Supports standard UVC and UAC protocols.
3. The LED will light up when the app is using the webcam.

Video Format

Outputs both MJPG and YUY2 compression video

capable of supporting 3840*2160@30fps and

1920*1080@60fps. Supports Windows, Mac OSX, Android

Chrome and Linux operating systems.

MJPG

Portrait video	1080*1920@30/15 720*1280@30/15 576*1024@30/15 360*480@30/15
Landscape video	4000*3000@15/10 3840*2160@30/10 2560*1440@20/10 1920*1080@60/30 1280*720@60/30 1024*576@60/30 640*480@20/10

YUY2


1280*720@12/5 1024*576@20/10 640*480@30/20
--

Mic Parameters


Built-in Microphone with Noise Cancellation.

Sensitivity: $-26\pm 2\text{dB RL}=2.2\text{K}\Omega V_s=2.0\text{V}$

Omnidirectional microphone



Installation Mode



A. The webcam is fixed on the tripod

(sold separately).

B. The webcam is fixed to the top of the display.

Size & Weight

Webcam Size: 89mm \times ϕ 45mm

Package Size: 110mm \times 70mm \times 93.5mm

Net Weight: 0.16kg

Gross Weight: 0.27kg

Webcam size

